

# Concrete Dam Flood Monitoring Interface™ Mini's

Industry: Infrastructure

## Summary

Customer Need / Challenge	Interface Solution	Results
A customer wants to monitor and be notified if a concrete dam has reached high flooding levels.	Interface's WMC Miniature Sealed Stainless Steel Load Cells with multiple WTS-AM-1E Wireless Acquisition Modules connected to them, are small in size and perfect for measuring tension and compression. Multiple WMC's can be installed around the arch of the dam, so when flooding occurs, the WMC can transmit data and notify the customer through one of our Wireless Telemetry Systems.	The customer was notified wirelessly when flood level became too high for the dam in their control center.

## Materials

- WMC Miniature Sealed Stainless Steel Load Cells
- WTS-AM-1E Wireless Acquisition Modules
- WTS-BS-4 USB Industrial Base Station
- WTS-BS-1-HS Wireless Handheld Display for Single Transmitters
- Customer PC Computer or Laptop

## How It Works

1. Multiple WMC Miniature Sealed Stainless Steel Load Cells with multiple WTS-AM-1E Wireless Acquisition Modules connected to them, are anchored to the concrete dam at the maximum height preferred.
2. If flooding occurs, the force from the water triggers the WMC's, and data is transmitted wirelessly to the customer's WTS-BS-1-HS Wireless Handheld Display for single transmitters.
3. Data can also be sent to the customer's control center through the WTS-BS-4 USB Industrial Base Station, when attached to the customer's PC Computer or laptop.

